

# AEROBRIL

## ANTICORROSION GLOSS PAINT



### 7 good reasons for using AEROBRIL

1. Excellent coverage and filling properties.
2. High **resistance** to the weather, U.Vs and chemical products.
3. Exceptional **surface hardness**.
4. **Rapid** drying.
5. Durable **high-gloss** finish.
6. Excellent **anti-corrosion** properties.
7. Heat resistant up to **120 °C**.

### Particularly suitable for use in :



Public buildings



Industry



Construction

High-gloss top coat.

For use on all metals that can usually be painted: sheet steel, bodywork, cast iron, but also on wood, glass and terracotta.

Characteristics	Instructions for use
<p>Modified alkyd paint Family 1 Class 4a Drying time: Touch dry/dust free: 30 min Dry-through: 3 hours Coverage per aerosol can around 2m<sup>2</sup> Net volume: 400 ml</p> <p>STANDARD RAL COLOURS - White 9010 - Black 9005 - Yellow 1021 - Red 3000 * RAL shades (on request)</p> <p>For more information, see MSDS.</p>	<p>Surface must be free of rust, dust or grease before application. Protect the surrounding areas which are not to be painted. <b>Shake vigorously before use (at least 30 seconds).</b> Spray the object to be painted from a distance of 25 to 30 cm on the object to be painted holding the aerosol vertically.</p> <p>The best result is obtained by applying 2 or 3 thin coats. Wait a few minutes between each coat, but no more than 30 minutes. After 24 hours, remove the overspray with a polishing paste. After use, purge the valve by spraying upside down.</p>

GB16122016

7 +

**SOLVCLEAN:** Degreaser for surface preparation

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00  
www.7darmor.fr

**7d'Armor**