



# AQUASOLV NG

FOOD SECTOR  
CLEANING SOLVENT

NEW  
GENERATION



Nonfood Compounds  
K1, K2



## 7 good reasons for using AQUASOLV NG

1. AQUASOLV NG is an excellent degreaser for metal parts.
2. Can be mixed with water in any proportions.
3. Dissolves a large variety of substances such as grease, oil and resin.
4. Excellent **substitute** for degreasing solvents, such as trichlorethylene, perchloroethylene, toluene or xylene. Does not contain chlorinated solvents.
5. **Safe use**: no special classification for users or the environment.
6. **Neutral** and universal (has a wide spectrum of efficiency, compatible with most materials and seals).
7. May be used for cleaning surfaces in contact with **foodstuffs** (after rinsing).



## Particularly suitable for use in



Industry



Agri-Food Industry

Specially designed for degreasing metal parts (preparation of surfaces before painting, glueing or any other applications...).

Dissolves grease from stored mechanical parts.

Dissolves marks from stickers and glue.

Technical fluid for degreasing operations.

Effective on fresh paint (with mechanical action): it is used as a coalescing agent and as a co-solvents in paints / solubilising action : subject to testing according to the type of polymer component in the paint (only on mono-component – acrylic or glycerophthalic type – doesn't work on epoxy, polyurethanes). Can be used to clean paint application tools.

| Technical Specifications  | Instructions for use   |
|---|--|
| <p>Colourless liquid<br/>Density: 1.007<br/>Flash point: &gt;60°C</p> <p>Complies with the legislation on cleaning products for equipment that may come into contact with foodstuffs (Decree of 08/09/1999 and its amendments).</p> | <p>May be used diluted with water or neat.<br/>Apply by spraying with a cloth or immersion.<br/>Wipe and rinse if necessary.<br/>We recommend, given the very wide diversity of surfaces and surface treatment, to always do a preliminary test. For all contact with plastics, do a preliminary test. AQUASOLV NG can render some plastics brittle.<br/>May be used in degreasing fountains, neat or diluted, in FONT INOX HP, FONT INOX, SOLVENT FOUNTAIN fountains.<br/>May be used in diswashers for mechanical parts, neat or diluted.<br/>May be used in ultrasound baths, neat or diluted.<br/>Product non considered dangerous according to current regulations.<br/>For more information, see MSDS.</p> |

GB26112025

**BD10** : multi-purpose ecological lubricant.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.



Tél 02 97 54 50 00  
Www.7darmor.fr

