



BITU PRIM

**BLACK BITUMEN EMULSION
FOR COLD FILLERS**



7 good reasons for using BITU PRIM

1. Black bitumen emulsion.
2. Can be used from 5°C.
3. Tack coat before filling with BITUROUTE.
4. Improves cold fillers' adherence.
5. Sealing and waterproofing product for foundations.
6. Rapid. No drying time (for repairs with BITUROUTE).
7. Adheres to all surfaces.

Particularly suitable for use in



Public buildings



Services



Constructions

Characteristics	Instructions for use
<p>Coverage: 150 to 300 gr/m² No drying time. Apply the filler directly. pH: 2 to 4 Density: 0.95-1 To clean equipment: use solvent</p> <p>Colour: black</p> <p>For more informations: see MSDS.</p>	<p>Shake the product well before use. Apply the product with a brush, roller or broom. Pour <u>the cold filler</u> (BITUROUTE) immediately into the hole to be filled. BITUPRIM can also be used as a joint between the BITUROUTE and the asphalt. In such cases, we recommended 'dusting' with clay filler (or porphyry) to eliminate the product's stickiness.</p> <p>IMPORTANT: the colder it is, the longer it will take the product to dry (for joints). Resumption of traffic depends on the size of the repair and the exterior temperature. The surface must be dry. Must be stored in closed original packaging between 5°C to 25° C Storage time: 1 year</p>

GB22112021/1

7 +

MULBIO NG: Ready to use tar remover.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.



Tél 02 97 54 50 00
 Www.7darmor.fr

