

DETARTRAL N

SAFE DESCALER FOR WATER CIRCUIT





7 good reasons for using **DETARTRAL NT**

- 1. Contains corrosion inhibitors.
- 2. Mixes instantly with water.
- 3. The solution remains stable during descaling.
- 4. Does not give off any harmful or corrosive vapours.
- 5. Does not corrode ferrous metals.
- 6. No risk for alloys after rinsing,
- 7. Inert on plastics, rubbers and seals.

Particularly suitable for use in:



Agro-Food Industry.





Descaling of washing-up machines, washing machines, coffee-machines, water-heaters as well as recep-

Maintenance of sanitary systems, baths, tiled-floors in showers.

Characteristics

Composition: Sulphamidic acid in solution, corrosion

inhibitors.

Density 1.08 ± 0.01 Colour colourless 1.5 рΗ

Complies with legislation on cleaning products for equipment which may come into contact with foodstuffs (Decree dated 08/09/1999 and its amendments).

Instructions for use

For descaling, pour the product diluted to10-20% concentration into the circuit. Leave the product on for 15 to 20 minutes, drain the circuit and

For maintenance of sanitary systems, dilute one volume of DETARTRAL NT to 5 to 7 volumes of water. Spray the solution on the surface to be descaled. Leave the product on for a few minutes and rinse with water.

For more information, see MSDS

GB23012024/6

7 +

KLIMKOS: Liquid caustic cleaner for pipes

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00 Www.7darmor.fr

