



HYDROSINE 43

UNIVERSAL DEGREASER IN FOUNTAIN



7 good reasons for using HYDROSINE 43

1. High quality **degreaser** and high quality solvent for oils.
2. Based on disaromatized hydrocarbonaceous solvents. Does not contain chlorinated solvent.
3. Does not corrode **joints, plastics, nor paints**.
4. No **corrosion** on metals.
5. **No deposit** after evaporation.
6. Is mainly used in degreasing fountains.
7. Dries **rapidly**.

Particularly suitable for use in:



Industry



Public buildings

Cleans, degreases all mechanical parts.
 Eliminates dirty oils, oil, fats, as well as fuel oil.
 Allows the cleaning of electric unit it switched off.
 Is mainly used in degreasing fountains.

Characteristics	DEGREASING FOUNTAIN	Instruction for use
<p>Appearance: transparent liquid Density at 20°C: 0.78 Flash point: 43°C Kauri-butanol Index: 32</p> <p>For more information, see MSDS.</p>		<p>IN DEGREASING FOUNTAIN After switching on the pump, rub parts with the brush till clean. Leave to dry by evaporation.</p>

GB27032023/5

7 +

BD10: multi-purposes, plant base.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

