

TRACER PAINT

FLOOR SIGN PAINTS



Gun 'Tracer'



7 good reasons for using TRACER PAINT

1. Very good **resistance** in various weather conditions and U.Vs.
2. Assures **long-lasting** marking.
3. **Clean** to use.
4. Reliable and **regular output**.
5. **Easy to use** for manual application with a gun, thanks to its ergonomic lid.
6. **Free** from aromatic and chlorinated solvents.
7. **6 colours**: standard white and yellow plus blue, red, green and black.

Particularly suitable for use in



Public buildings



Services

To paint lines on floors, in Industry, Shopping centres, in schools, carriers.
To define parking spaces, work stations in workshops, pedestrian traffic lanes, storage areas.
To define playgrounds, sport fields, tennis court boundaries.
Can be applied inside or outside to cement, bitumen, asphalt, wood, painted surfaces.

Characteristics	Marking trolley	Instructions for use
<p>Composition: acrylic binder, mineral and organic pigments, lead and cadmium free, Solvents: complex mixture without chlorinated aromatic solvents. Drying time: 15 - 20 mn Use temperature: +5°C to 50°C</p> <p>Marking lifetime: approximately 12 months according to surfaces and traffic. Lines tracing (slow stroke): 1 coat 50 m, 2 coats: 25 m Lines tracing (fast stroke): 1 coat 75 m, 2 coats: 37 m Propellant gas: mix isobutane and propane Net volume: 500 ml</p> <p>STORAGE AND HANDLING: Sprayers must be kept between 15°C and 25 °C and between 50 and 60% of relative humidity. Do not expose to temperatures exceeding 50°C.</p> <p>For more information, see MSDS.</p>		<p>Shake the spray upside down before each use to mix the paint well and hear balls clearly. Adapt the nozzle to the spray. Place the spray on the marking trolley. Use upside down, adjust the application height to the equipment used according to the required width of line.</p> <p>AFTER USE: purge with the spray in the upright position (until there is only gas coming out) to clean valve and sprayer.</p> <p><u>General terms of use:</u> for whatever type floor, the following conditions are required for a correct application of TRACER PAINT. In order to obtain an excellent paint adhesion, the surface to painted must be prepared well. Clean the surface thoroughly to eliminate dusts, stains, grease... The hydrometry level must be between 10 and 50%. The use temperature mustn't be lower than 5°C. For a high quality line, the first stroke must be applied quickly (undercoat), however the second and possibly the third strokes should be applied more slowly to obtain the required coverage.</p> <p><u>Recommendations for floor type:</u> CONCRETE: Before painting, it is necessary to wait 3 to 4 weeks, so that the concrete is completely dry and the acidity eliminated (standard DTU). ASPHALT: it is recommended to wait at least 15 days before applying to a new asphalt coat to preserve the quality of the marking. For the SYNTHETIC AND PAINTED floors, it is recommended to do a preliminary test.</p>

GB13042023/2

7 +

STADE LINE : Sign paints for sport fields.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor