



USILUB T

MACHINING AND THREADING OIL



7 good reasons for using USILUB T

1. **Extreme pressure** oil. Powerful **friction reducing agent**.
2. Ensures **excellent surface conditions**.
3. **Lubricating**, prolongs tool life.
4. **Protective film**, reduces the risk of jamming between the tool and the part.
5. Facilitates the evacuation of **filings**.
6. Leaves a thin oily film, which **protects** the machined surfaces.
7. The aerosol ensures **precise** application.

Particularly suitable for use in



Industry



Public buildings



Transport

Particularly effective for eliminating metal pullout and marring on tools.

- cold machining of stainless or refractory steels.
- threading, drilling, stamping of very thick pieces.
- cutting, contouring of thick strips, in dies or on rollers.

Characteristics	WYPNET	Instructions for use
<p>Composition: mixture of mineral oils and extreme pressure additives Appearance: liquid at 20°C, black colour Viscosity: 70 Cst at 40°C Propellant gas: CO₂ Volume: 400 ml (650ml) Volume: 400 ml (650ml)</p> <p>For more information, see MSDS.</p>		<p>Shake the aerosol before use. Spray approximately 5 to 10 cm from the surface to be lubricated. Repeat if necessary.</p>

GB08112019

7 +

DEVIT : Anti-corrosion penetrating lubricant.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
 Www.7darmor.fr

