# ALUCOL

## ADHESIVE STRIP OF COLD WATERTIGHNESS

2 colours
**LIGHT GREY**
**DARK GREY**

## 7 good reasons to use **ALUCOL**

1. Complex **multi-layer** composed of:
   A layer of mastic butyl adhesive.
   Untearable aluminium film.
2. The adhesive face is protected by **silicone peel-off.**
3. Resists to temperature up to **80°C**.
4. Has an excellent **adhesion** and a very good **resistance** for the cutting.
5. Always applied **cold**.
6. Does not contain **asphalt**.
7. Adheres to building **surfaces**, concrete, aluminium, glass.

## Particularly suitable for use in

Construction Institutions

Waterproof joints in industry, maintenance, construction.
Maintenance of the roof ridges, terraces.
Repair work to guttering.
Is used on air conditioning, ventilation pipes.

| Technical Specifications | Instruction for use |
|---|---|
| Roll: length 10m, width 20cm<br>Thickness: around 0.6mm<br>Area density : around 1000g/m²<br>Peel strength (angle 90°/100mm/mm) on steel (MEL052) : F≥ 4N/cm<br>Water vapour permeability (NF T30-018) : around 2.5g/m²/24h representing a value <SD> of 2500m.<br>Resistance casting of mastic butyl to:<br>. 5°C (ISO7390): < 3mm<br>. 70°C (ISO7390): < 3mm<br>Temperature for application: +5°C ≤ T ≤+40°C<br>Service temperature: -30°C ≤ T ≤+80°C<br>2 colours : light grey (colour aluminium) and dark grey (colour lead)<br><br>For more information, see MSDS. | Supports must be clean, dry and dusted.<br><br>Cut the strip to the desired length. Remove the protective film and apply to the support. Press sharply to avoid air bubbles.<br><br>If the strip is not wide enough, it's possible to overlap by 5 mm.<br><br>Do not apply to frozen supports. |

GB10012023/5

**7 +**
**HYDROCIDE** : Surface water-proofing product

Our cardboard packaging is recyclable and is produced with respect for forests according to the FSC label. Our plastic is easily recyclable.
This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non contractual photos and images.

Tél 02 97 54 50 00
www.7darmor.fr

7 d'Armor

7 d'Armor® takes the utmost care in prepairin the order and the product quality. In case of defect accepted by the company, its obligation will be limited exclusively to product replacement or refund of defected quantities without other compensation.
Defects and damage resulting from storage, handling, transport or use are excluded from the warranty in irregular conditions not conformed with the nature, prescriptions as well as the product use not respected the instructions of the technical data sheet.