

CALCIM VG

CEMENT FILM REMOVER



7 good reasons to use CALCIM VG

1. CALCIM VG is a **new-generation** cleaner that **rapidly** removes fresh cement or concrete film, limescale and white “efflorescence”.
2. **No safety** classification for users.
3. Meets various user requirements for **safety**, efficiency, environmental impact and care of treated surfaces.
4. CALCIM VG is much less corrosive than other products on the market.
5. **70% biodegradable** after 28 days.
6. **Ready** to use, easy and fast application.
7. Can be used indoors and outdoors.

Particularly suitable for use in



Construction



Industry



Public buildings

Ideal for cleaning floors and walls of concrete, natural or reconstituted stone, terracotta or tile....

For cleaning public works equipment, concrete mixer trucks, formwork, concrete plants for fresh concrete soiling.

For cleaning after laying tiles, cement floors and concrete surfaces.

For descaling for heating and cooling systems and reservoirs.

Characteristics	Instructions for use
Formulated with natural ingredients. Physical state at 20 °C: Liquid Colour: colourless/pale yellow Odour: Lemon pH: <2 Density: 1.07 ± 0.05 Average yield for information: 3 to 6 m ² /litre Solubility in water [vol/vol]: Total Flash point [°C]: NC For more information, see MSDS.	<u>Preliminary spot tests must be carried out.</u> Shake well before use. Use CALCIM VG neat. Apply the product using a low-pressure sprayer like JUMBO 6 or JUMBO 2000), or a manual spray or a brush. Leave the product on for 5 minutes whilst brushing with a stiff brush for a better result. Do not allow the product to dry before rinsing. Rinse the entire surface with a high-pressure spray once the deposits have dissolved. We recommend treating the surface after cleaning and drying with our preventive solution PROTECT 7 in order to avoid further soiling. NOTA : on concrete, blue limestone or reconstituted stone, wet the surface before applying the product in diluted form (equal quantity of product to water). Leave the product to work for less than 3 minutes. See recommendations overleaf.

GB2202024/1

7 +

PROTECT 7 : Water/oil repellent, antifouling

Our cardboard packaging is recyclable and is produced with respect for forests according to the FSC label. Our plastic is easily recyclable. This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
Www.7darmor.fr

7d'Armor

CLEANING OF EQUIPMENT

Clean tools and equipment with water immediately after use.

STORAGE

Store in a dry place at a temperature between 5°C and 30°C.

Shelf life: 48 months from the manufacturing date, in unopened original container.

RECOMMENDATIONS

- CALCIM VG is a safe product but prolonged contact with skin can cause irritation. Wear gloves and protective clothing and glasses.
- Do not mix with other substances, in particular bleach (risk of release of toxic chlorine gas).
- Do not allow the product to dry.
- For indoor use, apply the product in a well-ventilated area.
- Protect metal surfaces (aluminium, zinc, tin, copper, light alloys...) and glass.
- On concrete, blue limestone or reconstituted stone, wet the surface before applying the product I, diluted form (equal quantity of product to water). Leave the product to work for less than 3 minutes. Always carry out a preliminary spot test.
- Do not apply on marble or polished or crystallised material.
- For perfect application, it is imperative to use the product when the temperature of the surface to be treated is between 5°C and 30°C.
- Do not apply when it is raining or in very hot weather.

