



SYNER 150

**SOLVENT DEGREASING
SOLUBLE IN WATER
POWERFUL**

7 good reasons for using SYNER 150

1. **Deep** cleaning of floors, emulsifies the strongest greases and oils.
2. For **cleaning** all industrial equipment with varied and stubborn marks (mineral greases, vegetal, soil ...).
3. Soluble in water, **economical**: can be diluted from 2 to 20% according to the surfaces.
4. **Renews** plastic surfaces such as: benches, chairs, tables, window frames, doors.
5. Without damaging usual materials (Stone floors, plastics, painted surfaces).
6. Used in a 5 points **HACCP** process for degreasing.
7. Complies with the legislation on cleaning products for equipment that may come into contact with **foodstuffs** (Decree of 08/09/1999 and its amendments). Mandatory rinsing.

Particularly suitable for use in



Public buildings



Industry



Transport



F.P.I.



Construction

Industry: degreases industrial equipment, machine frames. Cleans walls and grounds, concrete, spare parts and precision instruments. Degreases metals before stripping. Cleans all internal and external equipment and is used to remove mud from cooling circuits and lubrication circuits on towers, rolling mills, planning machine. Is adapted to the cleaning of machine tools during the change of cooler.

Construction: Degreasing floors before painting. Wallpaper removal. For cleaning boilers and heating elements.

Automotive: Degreases tank parts, vapour pipes, tanks, the oil tanks of refineries.

Foodstuff Industries: Bakeries, canning factory, breeding; removes fats and deposits on manufacturing, packing or bottling machines. Clean hoods, filtering and ventilation systems.

Towns: multi-purpose degreasing, cleans engines, pumps, street safety markers, concrete floors and hydraulic or purification stations equipment. Ideal for cleaning heads of parkingmeters. Removes posters.

Printing works: Eliminates grease and ink on all metallic surfaces of printing presses.

Characteristics		Instructions for use
Appearance	Liquid	<p>By dip tank or by spraying Use diluted from 2 to 15% depending on the dirtiness. Spray the surface to be treated so that it is completely covered with the product and let it take effect for a few seconds. Dry and rinse.</p> <p>For automatic floor-cleaner Use diluted from 0.5 to 2%.</p> <p>For pressure material Use diluted from 1 to 3 % (by hose).</p> <p>For cleaning of boilers and heating elements. Spray with 1l of SYNER 150 for 5l of water on the warm surface (60°C). Heat 2 or 3 minutes. The greyish deposits come off the boiler brush. Eliminates the residues with the suction material.</p> <p>Gloves and glasses are strongly recommended during the use of the product. SYNER 150 can stain glass and anodized aluminium.</p>
Colour	Fluorescent yellow	
pH of the neat product	13.20 ± 0.010	
Density	1.052 at 20°C	
Flash point	None	
Composition:	Not ionic surfactants, holding, oxygenated solvent, corrosion inhibitors, alkaline mineral salts.	
For more information, see MSDS.		

GB23012024/5

7 +

MONOSOL : Industrial floor paint.

This datasheet supersedes previous documents. The information contained in these data sheets is based on our present knowledge and experience and is given as indication only. Under no circumstances does it engage our responsibility in the event of misuse of our products. Non-contractual photos and images.



Tél 02 97 54 50 00
www.7darmor.fr

7d'Armor